# BREATHE FREELY Australia

Controlling Exposures to prevent occupational lung disease in the construction industry



# Stonemason , also see the Engineered Stone Sheet

### **HAZARDS AND RISKS**

### **CONTROL OPTIONS**

#### When different types of stone are worked by cutting, grinding and chiselling with hand and power tools, airborne dust is generated that can cause serious lung conditions if inhaled over time. Some stonemasonry trades may involve the application of fine decorative detail to stone, which often requires working very closely to the dust source.

# Stone dust and respirable crystalline silica (RCS)

Stone dust contains varying amounts of silica, and comprises a mixture of different sized particles. Breathing in the smaller respirable sized fraction of the silica dust – respirable crystalline silica (RCS) - can result in the development of serious lung diseases, including fibrosis, silicosis, chronic obstructive pulmonary disease (COPD) and lung cancer. These diseases may cause permanent disability and early death, and it is estimated in Australia that over 230 workers die every year from exposure to silica dust. Inhaling any dust can lead to lung irritation, asthma and other acute and chronic respirable conditions.

#### Engineering controls Local exhaust ventilation (LEV):

- Enclose the dusty process in a down draught or cross draught booth so that dust laden air is drawn away from the work area.
- Use "on-tool" LEV: also known as a "shroud" which encloses the grinding wheel. A vacuum source is attached to the shroud to remove dust generated by the grinder at the source of emission.

## Safe working methods

#### Water suppression:

 Pre-soak stone to minimise dust creation and apply running water to the process via on-tool suppression to further reduce exposures.

#### PPE

- Risk assess the tasks and also refer to the Australian Standard AS/NZ 1715 for RPE guidance.
- Respiratory protective equipment (RPE) with at least a P2 performance is required for high silica content materials. Risk assess where high dust levels and consider wearing a PAPR RPE. Wearers must be face fit tested to ensure the RPE affords each individual the anticipated level of protection.

#### Preferred control measures

• Water suppression with supplemental RPE. On tool LEV with supplemental RPE for grinding work.

### **MANAGING THE RISK**

#### Training & communication, supervision, maintenance & testing of controls and air

**monitoring**<sup>\*</sup> are all vital aspects of managing the risk, in addition to health surveillance which can be a requirement in certain circumstances.

See our introductory Respiratory Health Hazards in Construction Fact Sheet Series: **Overview** for more information about what things to consider and implement.

#### Air monitoring\*

Air monitoring is a specialist activity. It may be needed as part of a risk assessment, as a periodic check on control effectiveness and to assess compliance with relevant WES, or where there has been a failure in a control (for example if a worker reports respiratory symptoms). A qualified Occupational Hygienist can ensure it is carried out in a way that provides meaningful and helpful results.



# Stonemason

# WORKPLACE EXPOSURE STANDARDS (WES) & EXPOSURE LEVELS

Agent or substance	Control/Exposure Limit	Exposure Levels
Silica - RCS	0.05 mg/m³ (8 hr TWA).	Exposure to RCS is dependent on the silica content of the material being worked, which varies. Sandstone (70-90% silica) and concrete (25-75% silica) typically contain the most. Granite, slate and brick (around 30% silica); and limestone and marble (around 2%) usually contain the least. Grinding and cutting without water suppression is likely to produce the highest levels of stone dust, and risk of exposure to RCS is also affected by the frequency and duration of the work.

# Personal exposure monitoring of stonemasons working over sampling periods representative of full shift exposure have demonstrated the following levels of exposure to RCS.

Material and Task	No. of samples	GM	RCS range 8hr TWA mg/m3
Sandstone	55	0.14	<0.02-6.00
Cutting angle grinder	10	0.70	0.26-1.30
Cutting water-cooled primary saw	16	0.02	<0.02-0.13
Grinding angle grinder	2	0.70	<0.02-6.00
Decoration hand and pneumatic chisel	7	0.008	<0.02-0.07
Limestone	15	0.008	<0.02-0.03
Cutting angle grinder	1	0.01	<0.02
Grinding angle grinder	7	0.008	<0.02
Decoration hand and pneumatic chisel	7	0.007	<0.02-0.03
Lime Mortar	23	0.005	<0.02-0.06
Repointing	23	0.005	<0.02-0.06
Granite	10	0.03	<0.02-0.21
Cutting water-cooled primary saw	4	0.01	<0.02-0.03
Grinding angle grinder	6	0.06	<0.02-0.21

## Further HSE information

• COSHH essentials for stonemasons: hand held rotary tools: www.hse.gov.uk/pubns/guidance/st3.pdf

